



MKV46F256VLL15

RoHS
 4588 pcs stock
 Hong Kong
 DHL/Fedex/TNT/UPS/EMS

24
 info@global-ic.hk

MKV46F256VLL15

Operating Voltage (Vcc / Vdd)	1.71V ~ 3.6V	Package	100-LQFP (14x14)
Frequency	150MHz	Core	Kinetis KV
RAM	32K x 8	Memory	FLASH
Flash Memory	256KB (256K x 8)	Peripherals	DMA, LVD, POR, PWM, WDT
Package	100-LQFP	Mounting	Tray
Memory Location	Internal	Temperature Range	-40°C ~ 105°C (TA)
I/O Pins	74	Mounting Style	Surface Mount
EEPROM	-	Converters	A/D 16x12b; D/A 1x12b
Architecture	32-Bit Single-Core	Processor	ARM® Cortex®-M4
Interfaces	CANbus, I ² C, SPI, UART/USART	Part Number	MKV46F256

News



MOSER
 2023/07/4

2023/04/5

2023/07/21

800nm 800 3.13
 2023/08/30

2023/08/11

1%
 2023/09/18 2023/09/12

SIC Calteha, MMWAVE I
 2023/08/31 2023/09/11

TDK Kud Dcd Psus 5v
 2023/09/15 2023/08/17

PV
 2023/09/7